

EAT•N

Powerware

Powerware 5115 Uninterruptible Power System

Product Focus

500-1400 VA advanced power protection
for office servers



Product Snapshot

Power Rating:	500-1400 VA
Voltage:	240 VAC
Frequency:	50 Hz
Configuration:	Plug-and-play tower
Topology:	Line-interactive

Features

- High performance protection
- Software Suite bundled
- ABM™, prolongs battery life by 50%
- Hot-swappable user replaceable batteries
- Australian output sockets eliminate messy adaptors
- Standard USB and RS232 serial ports extend communication capacity

Options

- ConnectUPS-E external Web/SNMP adaptor

Typical Applications

- Small office servers
- High-capacity PCs and workstations

Designed to offer advanced power protection for office servers and other critical applications, Powerware 5115 protects your equipment against five of the nine most common power problems that can harm your equipment or result in corrupted data.

In offices a crucial part of the work is stored on servers and reliable shutdown software is needed to ensure that no data is lost even during longer power outages. With Powerware 5115 and LanSafe III protecting the server, business goes on while the UPS invisibly and automatically takes care that no data is lost due to power problems. If a total outage threatens to exceed the system's backup time, LanSafe III software automatically shuts down the entire network in a predefined order.

Technical Specifications

POWERWARE 5115				
Rating	500VA	750VA	1000VA	1400VA
Part number	51150500A	51150750A	51151000A	51151400A
Capacity (VA/Watts)	500/320	750/500	1000/670	1400/950
Dimensions WxDxH (mm)	150x268x185	150x333x185	150x333x185	150x388x185
Weight (kg)	8	12	13	17
Input connection	IEC320/10A	IEC320/10A	IEC320/10A	IEC320/10A
Output connection	3 x Aust. 10A	3 x Aust. 10A	3 x Aust. 10A	3 x Aust. 10A
Typical runtime (Full load)	5 min	6 min	5 min	5 min
Operational				
Nominal input voltage (Vac)	240 Vac			
Input voltage range	192 - 288 VAC (+/-20%)			
Operating frequency	50/60 Hz auto sensing			
Input power factor	Same as load			
Output voltage	240 Vac			
Output voltage regulation	216-254 VAC (-10%/+6%) or +/-5% on battery			
Overload capacity	110% 3 min; 150% 10 cycles			
Efficiency	95%			
User interface				
LED	Four LEDs; UPS on, UPS on battery, overload, alarm			
Standard communication ports	1 x RS232 & 1 x USB Port			
Optional	External SNMP adaptor			
Environmental				
Operating temperature	0°C to +40°C			
Storage temperature	-15°C to +55°C			
Altitude	< 3000 m			
Audible noise at 1 metre	< 40dB			
Certification				
Markings	CE/GS/UL/C-Tick			
Safety	EN 50091-1-1 & IEC 609050			
EMC (Class B)	AS62040.2.2001, C-Tick			
Battery Runtimes in minutes				
Load	51150500A	51150750A	51151000A	51151400A
200VA/128W	17	38	41	58
300VA/192W	11	27	28	41
500VA/320W	5	14	15	28
600VA/402W	-	9	10	19
750VA/503W	-	6	8	14
900VA/603W	-	-	6	10
1000VA/670W	-	-	5	8
1200VA/804W	-	-	-	6
1440VA/938W	-	-	-	5

This guide provides typical application information. Battery run times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

In the interests of continual product improvement all specifications are subject to change without notice.

Eaton, Powerware, Hot Sync, Advanced Battery Management, LanSafe, PowerVision, and FORESEER are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates. © 2007 Eaton Corporation, All Rights Reserved.



**NPS Head Office
NSW**
Unit 8
2-6 Waltham Street
Artarmon NSW 2064
P: 02 9906 6696
F: 02 9906 6434

NPS – VIC
Unit 1
40 Jellicio Drive
Scoresby VIC 3179
P: 03 9764 8550
F: 03 9764 8770

NPS – QLD
Unit 8
210 Queensport Road
Murarrie QLD 4172
P: 07 3907 0222
F: 07 3907 0333

NPS – SA
PO Box 406
Kilkenny SA 5009
P: 08 7200 2350
F: 08 7200 2360

NPS – WA
Unit 34
110 Inspiration Drive
Wangara WA 6065
P: 08 9302 6366
F: 08 6210 5915

www.nps.com.au



Powerware